

Our exclusive South African partner



**BestWood Flooring**

Cape Town showroom

50 Buitenkant Street, Cape Town

Tel: 021 465 1035

Mail: [capetown@bestwood.co.za](mailto:capetown@bestwood.co.za)

[www.bestwood.co.za](http://www.bestwood.co.za)



ADDRESS  
Leemansstraat 2  
4251 LD Werkendam  
Netherlands

CONTACT  
+31 183 504 266  
info@hakwoodcomplete.com

## HAKWOOD COMPLETE CLEAN

HAKWOOD COMPLETE CLEAN is a professional water based cleaning fluid, specially formulated for the regular & periodic (deep) cleaning of Hakwood prefinished floors.

The whole area can be cleaned using a conventional bucket & mop, a spray in combination with a mop or by use of a professional wood floor cleaning machine.

1. Sweep, dust mop or vacuum before cleaning with Hakwood Complete CLEAN.
2. Shake the container well before use.
3. For routine cleaning and maintenance
  - Dilute Hakwood Complete CLEAN at a 1 to 50-100 ratio with clean, warm water, approx. 100-200 ml of CLEAN in 10 L of water.
  - For intensive cleaning – Dilute Hakwood Complete CLEAN at a 1 to 10 ratio with clean, warm water, approx. 1 L in 10 L of water. Work in sections. After intensive cleaning, damp-mop the surface with clean water to remove residue from floor.
4. Apply a thin, even coat in the direction of the wood planks using a microfiber mop or lint-free cloth. Recommendation: Rinse mop during cleaning process to avoid leaving a dirty residue behind.

### Important notes:

- HAKWOOD COMPLETE CLEAN is suitable for all Hakwood prefinished oiled & lacquered flooring.
- Hakwood floors must be recoated with HAKWOOD COMPLETE OIL CARE after every deep cleaning.
- Regular treatment with HAKWOOD COMPLETE CLEAN & HAKWOOD COMPLETE OIL CARE improves the visual appearance and increase the wear life of all Hakwood flooring.
- HAKWOOD COMPLETE CLEAN is skin friendly
- Stability: minimum 24 months.
- Store between 10 -20 °C or 50 ° – 70 F
- PH value – 7 (neutral)



**Basics:**

- The floor should then be swept with a soft brush or vacuumed with a vacuum cleaner
- Whatever protection a wooden floor has received it will be inevitably need protection & maintenance.
- The color of wooden floors will change over time depending on the type of finish, wood species and amount of exposure to direct sunlight, therefore protect the floor from direct sunlight.
- Good , well maintained entrance and barrier matting will help to prevent the ingress of water and dirt into the floor.
- Apply (slip resistant) runners or area rugs on high traffic areas.
- Use a dolly, rolled over plywood when moving heavy objects.
- The floor may expand and contract as seasons and humidity levels change.
- Hakwood flooring like the conditions we like, so constant temperature between 18 °C to 22 °C and humidity levels between 35% and 65% suit them best.
- All chairs and tables should be fitted with appropriate pads to avoid scratching
- Replace narrow, hard furniture rollers with wide rubber ones.
- Move area rugs occasionally as they block sunlight and may give the appearance of discoloring under the rug.
- Always clean the floor in accordance with the Hakwood Complete CLEAN & CARE Instructions.
- Remove any spillages as quickly as possible, if fluid is allowed to remain on the floor for any length of time, it could penetrate the finishing.
- Any sticky substance as chewing gum should be carefully removed from the surface.
- Large items of debris should be carefully collected by hand.



ADDRESS  
Leemansstraat 2  
4251 LD Werkendam  
Netherlands

CONTACT  
+31 183 504 266  
info@hakwoodcomplete.com

## HAKWOOD COMPLETE OIL CARE

Refreshes and protects wood floor surfaces finished by Hakwood.

HAKWOOD COMPLETE OIL CARE is a water based oil/wax emulsion. Application frequency depends on the floor's location and level of use. Hakwood Complete OIL CARE is not a daily care product

### DIRECTIONS

1. Sweep, dust mop or vacuum before using Hakwood Complete OIL CARE.

2. Shake the container well before use.

3. For routine care:

- Dilute Hakwood Complete OIL CARE at a 1 to 30 ratio with room temperature water, approx. 200-400 ml in 10 L of water.

For intensive care:

- Use Hakwood Complete OIL CARE at a more intense strength, up to undiluted, to restore finish to scratches and even out floor sheen.

4. Apply one damp (not wet), even coat in the direction of the wood planks using a microfiber mop or lint-free cloth.

5. Allow to dry. Floor is ready to be walked on after 60 minutes.

### Important notes:

- Suitable for oiled and sealed engineered Hakwood flooring.
- Hakwood Complete OIL CARE may be applied undiluted in heavy traffic areas or on floors that sustain heavy commercial wear
- Average application frequency for residential floors is approx. 6 months. Heavy use commercial areas may require more frequent use
- Hakwood floors treated with Hakwood Complete Oil Care can be cleaned with Hakwood Complete Clean 12 hours after application
- Regular maintenance with Hakwood Complete Oil Care improves the visual appearance and increases the wear life of prefinished Hakwood floors